Safe Work Australia - Code of Practice

Silicone oil M 20 low viscosity, 20 cSt



article number: **4010** Version: **GHS 2.0 en** Replaces version of: 2016-03-17 Version: (GHS 1)

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1	Product identifier						
	Identification of the substance	Silicone oil					
	Article number	4010					
	Registration number (REACH)	The substance does not require registration ac- cording to Regulation (EC) No 1907/2006 [REACH]					
	EC number	none					
	CAS number	63148-62-9					
1.2	Relevant identified uses of the substance or mix	cture and uses advised against					
	Identified uses:	laboratory chemical laboratory and analytical use					
1.3	Details of the supplier of the safety data sheet						
	Carl Roth GmbH + Co KG Schoemperlenstr. 3-5 D-76185 Karlsruhe Germany						
	Telephone: +49 (0) 721 - 56 06 0 Telefax: +49 (0) 721 - 56 06 149 e-mail: sicherheit@carlroth.de Website: www.carlroth.de						
	Competent person responsible for the safety data sheet	: Department Health, Safety and Environment					
	e-mail (competent person)	: sicherheit@carlroth.de					
1.4	Emergency telephone number						
	Emergency information service	Poison Centre Munich: +49/(0)89 19240					
SEC	SECTION 2: Hazards identification						

2.1 Classification of the substance or mixture

Classification acc. to GHS

Classification acc. to GHS							
	Section	Section Hazard class		Hazard state- ment			
	2.6	flammable liquid	(Flam. Liq. 4)	H227			

2.2 Label elements

Labelling GHS

Signal word Warning

date of compilation: 2016-03-17 Revision: 2019-03-29

Safe Work Australia - Code of Practice



Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

Hazard statements						
H227	Combustible liquid					
Precautionar	y statements					
Precautionary	y statements - prevention					
P210 P280	Keep away from heat/sparks/open flames/hot surfaces No smoking. Wear protective gloves/protective clothing/eye protection/face protection.					
Precautionary	y statements - response					
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction					
Precautionary	y statements - storage					
P403+P235	Store in a well-ventilated place. Keep cool.					
Precautionary	y statements - disposal					
P501	Dispose of contents/container to industrial combustion plant.					
Labelling of pack	ages where the contents do not exceed 125 ml					
Signal word: Warı	ning					
H227	Combustible liquid.					
P210 P280 P370+P378 P403+P235 P501	Keep away from heat/sparks/open flames/hot surfaces No smoking. Wear protective gloves/protective clothing/eye protection/face protection. In case of fire: Use sand, carbon dioxide or powder extinguisher for extinction. Store in a well-ventilated place. Keep cool. Dispose of contents/container to industrial combustion plant.					

2.3 Other hazards

There is no additional information.

SECTION 3: Composition/information on ingredients

3.1 Substances

Name of substance	Polydimethylsiloxane
Registration number (REACH)	The substance is exempted from the obligation to register
CAS number	63148-62-9
Molecular formula	(C ₂ H ₆ OSi)n
Molar mass	74.15 ^g / _{mol}

Impurities and additives, classification acc. to EU regulation

Name of substance	Identifier	Wt%	Classification acc. to 1272/2008/EC
Dodecamethylcyclohexasiloxane	CAS No 540-97-6 EC No 208-762-8 REACH Reg. No 01-2119517435-42-xxxx	≥0.1-≤3	

Safe Work Australia - Code of Practice



Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

Substance of Very High Concern (SVHC)						
Name of substance	CAS No	Wt%	Listed in	Remarks		
Dodecamethylcyclohexasiloxane	540-97-6	3	Candidate list	PBT A57d vPvB A57e		

Legend

Candidate list PBT A57d VPvB A57e Substances meeting the criteria referred to in Article 57 and for eventual inclusion in Annex XIV Persistent, Bioaccumulative and Toxic (article 57d) Very Persistent and very Bioaccumulative (article 57e)

SECTION 4: First aid measures

4.1 Description of first aid measures



General notes

Take off contaminated clothing.

Following inhalation

Provide fresh air. In all cases of doubt, or when symptoms persist, seek medical advice.

Following skin contact

Rinse skin with water/shower. In all cases of doubt, or when symptoms persist, seek medical advice.

Following eye contact

Rinse cautiously with water for several minutes. In all cases of doubt, or when symptoms persist, seek medical advice.

Following ingestion

Rinse mouth. Call a doctor if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Gastrointestinal complaints, Diarrhoea

4.3 Indication of any immediate medical attention and special treatment needed none

SECTION 5: Firefighting measures

5.1 Extinguishing media



Suitable extinguishing media

Co-ordinate fire-fighting measures to the fire surroundings water spray, foam, dry extinguishing powder, carbon dioxide (CO2)

Unsuitable extinguishing media

water jet

Safe Work Australia - Code of Practice

Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

5.2 Special hazards arising from the substance or mixture

Combustible. Heating may cause a fire or explosion. Vapours can form explosive mixtures with air.

Hazardous combustion products

In case of fire may be liberated: carbon monoxide (CO), carbon dioxide (CO2)

5.3 Advice for firefighters

Fight fire with normal precautions from a reasonable distance. Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures



For non-emergency personnel

Special danger of slipping by leaking/spilling product. Wearing of suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. Avoid contact with skin, eyes and clothes. Do not breathe vapour/spray. Avoidance of ignition sources.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Explosive properties.

6.3 Methods and material for containment and cleaning up

Advices on how to contain a spill

Covering of drains.

Advices on how to clean up a spill

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Other information relating to spills and releases

Place in appropriate containers for disposal.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Provision of sufficient ventilation.

• Measures to prevent fire as well as aerosol and dust generation



Keep away from sources of ignition - No smoking.

Take precautionary measures against static discharge.

Advice on general occupational hygiene

Wash hands before breaks and after work. Keep away from food, drink and animal feedingstuffs.





Safe Work Australia - Code of Practice

Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed.

Incompatible substances or mixtures

Observe hints for combined storage.

Consideration of other advice

• Ventilation requirements

Use local and general ventilation.

• Specific designs for storage rooms or vessels

Recommended storage temperature: 15 – 25 °C.

7.3 Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

National limit values

Occupational exposure limit values (Workplace Exposure Limits)

Data are not available.

Relevant DNELs/DMELs/PNECs and other threshold levels

• relevant DNELs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
Dodecamethylcyclo- hexasiloxane	540-97-6	DNEL	11 mg/m³	human, inhalatory	worker (in- dustry)	chronic - systemic ef- fects
Dodecamethylcyclo- hexasiloxane	540-97-6	DNEL	1.22 mg/m ³	human, inhalatory	worker (in- dustry)	chronic - local effects
Dodecamethylcyclo- hexasiloxane	540-97-6	DNEL	6.1 mg/m³	human, inhalatory	worker (in- dustry)	acute - local effects

• relevant PNECs of components of the mixture

Name of substance	CAS No	Endpoint	Threshold level	Environmental compartment	Exposure time
Dodecamethylcyclo- hexasiloxane	540-97-6	PNEC	1 ^{mg} / _l	sewage treatment plant (STP)	short-term (single in- stance)
Dodecamethylcyclo- hexasiloxane	540-97-6	PNEC	13 ^{mg} / _{kg}	freshwater sedi- ment	short-term (single in- stance)
Dodecamethylcyclo- hexasiloxane	540-97-6	PNEC	1.3 ^{mg} / _{kg}	marine sediment	short-term (single in- stance)
Dodecamethylcyclo- hexasiloxane	540-97-6	PNEC	3.77 ^{mg} / _{kg}	soil	short-term (single in- stance)



Safe Work Australia - Code of Practice

Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

8.2 Exposure controls

Individual protection measures (personal protective equipment)

Eye/face protection

Use safety goggle with side protection.

Skin protection



hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

• type of material

NBR (Nitrile rubber)

material thickness

>0,11 mm

• breakthrough times of the glove material

>480 minutes (permeation: level 6)

other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended.

Respiratory protection



Respiratory protection necessary at: Aerosol or mist formation. Type: A (against organic gases and vapours with a boiling point of > 65 °C , colour code: Brown). Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190).

Environmental exposure controls

Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance


Physical state	liquid (viscous)
Colour	colourless
Odour	odourless
Odour threshold	No data available



Safe Work Australia - Code of Practice

Silicone oil M 20 low viscosity, 20 cSt

article number: 4010



Water solubility

Solubility in hydrocarbons, aliphatic Solubility in hydrocarbons, aromatic Solubility in ethylene glycol Solubility in ethyl acetate Solubility in toluene Solubility in trichloroethylene <u>Partition coefficient</u> n-octanol/water (log KOW) Auto-ignition temperature Decomposition temperature Viscosity • kinematic viscosity Explosive properties

Oxidising properties

This information is not available. -70 °C This information is not available. 240 °C no data available not relevant (fluid)

this information is not available this information is not available not relevant This information is not available. 0.95 - 0.96 ^g/_{cm³} at 25 °C This information is not available. Not applicable Information on this property is not available. The study does not need to be conducted because the substance is known to be insoluble in water soluble

soluble

practically insoluble

soluble

soluble

soluble

This information is not available. Information on this property is not available. >150 °C

18 – 22 ^{mm²}/_s at 25 °C Shall not be classified as explosive none



Safe Work Australia - Code of Practice



Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

9.2 Other information

SECTION 10: Stability and reactivity

10.1 Reactivity

In case of warming: Vapours can form explosive mixtures with air.

10.2 Chemical stability

The material is stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

10.3 Possibility of hazardous reactions Violent reaction with: Strong oxidiser

10.4 Conditions to avoid

Keep away from heat. Decompostion takes place from temperatures above: >150 °C.

10.5 Incompatible materials

There is no additional information.

10.6 Hazardous decomposition products

Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Shall not be classified as acutely toxic.

Exposure route	Endpoint Value		Species	Source
oral	LD50	>5,000 ^{mg} / _{kg}	rat	TOXNET

• Acute toxicity of components of the mixture

Name of substance	CAS No	Exposure route	ATE
Dodecamethylcyclohexasiloxane	540-97-6	oral	2,000 ^{mg} / _{kg}
Dodecamethylcyclohexasiloxane	540-97-6	dermal	2,000 ^{mg} / _{kg}

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitisation

Shall not be classified as a respiratory or skin sensitiser.

Summary of evaluation of the CMR properties

Shall not be classified as germ cell mutagenic, carcinogenic nor as a reproductive toxicant

• Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

• Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Safe Work Australia - Code of Practice

Silicone oil M 20 low viscosity, 20 cSt

article number: **4010**

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

Symptoms related to the physical, chemical and toxicological characteristics

• If swallowed

diarrhoea, gastrointestinal complaints

• If in eyes

data are not available

• If inhaled

data are not available

• If on skin

data are not available

Other information

None

SECTION 12: Ecological information

12.1 Toxicity

acc. to 1272/2008/EC: Shall not be classified as hazardous to the aquatic environment.

Aquatic toxicity (acute)

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Dodecamethylcyclo- hexasiloxane	540-97-6	ErC50	>2 ^{µg} / _l	algae	72 h
Dodecamethylcyclo- hexasiloxane	540-97-6	EC50	>2 ^{µg} / _l	algae	72 h

Aquatic toxicity (chronic)

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
Dodecamethylcyclo- hexasiloxane	540-97-6	EC50	>100 ^{mg} / _l	microorganisms	3 h

12.2 Process of degradability

Not readily biodegradable.

Degradability of components of the mixture

Name of sub- stance	CAS No	Process	Degradation rate	Time
Dodecamethylcyclo- hexasiloxane	540-97-6	carbon dioxide gener- ation	4.47 %	28 d

12.3 Bioaccumulative potential

The substance fulfils the very bioaccumulative criterion. Data are not available.



Safe Work Australia - Code of Practice



Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

Bioaccumulative potential of components of the mixture				
Name of sub- stance	CAS No	BCF	Log KOW	BOD5/COD
Dodecamethylcyclo- hexasiloxane	540-97-6	1,160	8.87 (23.6 °C)	

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment Data are not available.

12.6 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



This material and its container must be disposed of as hazardous waste. Dispose of contents/container in accordance with local/regional/national/international regulations.

Sewage disposal-relevant information

Do not empty into drains.

Sewage disposal-relevant information

Do not empty into drains.

13.2 Relevant provisions relating to waste

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

13.3 Remarks

Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities. Please consider the relevant national or regional provisions.

SECTION 14: Transport information 14.1 UN number (not subject to transport regulations) **14.2** UN proper shipping name not relevant **14.3** Transport hazard class(es) not relevant Class 14.4 Packing group not relevant not assigned to a packing group 14.5 Environmental hazards **none** (non-environmentally hazardous acc. to the dangerous goods regulations) Special precautions for user 14.6

There is no additional information.

Safe Work Australia - Code of Practice

Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

- **14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code** The cargo is not intended to be carried in bulk.
- 14.8 Information for each of the UN Model Regulations
 - Transport of dangerous goods by road, rail and inland waterway (ADR/RID/ADN) Not subject to ADR, RID and ADN.
 - International Maritime Dangerous Goods Code (IMDG)

Not subject to IMDG.

National inventories

• International Civil Aviation Organization (ICAO-IATA/DGR)

Not subject to ICAO-IATA.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Country	National inventories	Status	
AU	AICS	all ingredients are listed	
CA	DSL	all ingredients are listed	
CN	IECSC	all ingredients are listed	
EU	ECSI	all ingredients are listed	
EU	REACH Reg.	all ingredients are listed	
JP	CSCL-ENCS all ingredients are listed		
KR	KECI all ingredients are listed		
MX	INSQ	not all ingredients are listed	
NZ	NZIOC	all ingredients are listed	
PH	PICCS	all ingredients are listed	
TR	CICR all ingredients are listed		
TW	TCSI	TCSI all ingredients are listed	
US	TSCA all ingredients are listed		

Legend

AICS	Australian Inventory of Chemical Substances
CICR	Chemical Inventory and Control Regulation
CSCL-ENCS	List of Existing and New Chemical Substances (CSCL-ENCS)
DSL	Domestic Substances List (DSL)
ECSI	EC Substance Inventory (EÌNEĆS, ELINCS, NLP)
IECSC	Inventory of Existing Chemical Substances Produced or Imported in China
INSQ	National Inventory of Chemical Substances
KECI	Korea Existing Chemicals Inventory
NZIOC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
RFACH Reg.	REACH registered substances
TCSI	Taiwan Chemical Substance Inventory
TSCA	Toxic Substance Control Act

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance.



Safe Work Australia - Code of Practice



Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

SECTION 16: Other information

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
ADN	Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures (European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways)
ADR	Accord européen relatif au transport international des marchandises dangereuses par route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
ATE	Acute Toxicity Estimate
BCF	bioconcentration factor
BOD	Biochemical Oxygen Demand
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
CMR	Carcinogenic, Mutagenic or toxic for Reproduction
COD	chemical oxygen demand
DGR	Dangerous Goods Regulations (see IATA/DGR)
DMEL	Derived Minimal Effect Level
DNEL	Derived No-Effect Level
EC No	The EC Inventory (EINECS, ELINCS and the NLP-list) is the source for the seven-digit EC number, an identifier of substances commercially available within the EU (European Union)
EINECS	European Inventory of Existing Commercial Chemical Substances
ELINCS	European List of Notified Chemical Substances
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
ΙΑΤΑ	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
index No	the Index number is the identification code given to the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008
log KOW	n-octanol/water
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NLP	No-Longer Polymer
PBT	Persistent, Bioaccumulative and Toxic
PNEC	Predicted No-Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Règlement concernant le transport International ferroviaire des marchandises Dangereuses (Regulations concerning the International carriage of Dangerous goods by Rail)
vPvB	very Persistent and very Bioaccumulative

Key literature references and sources for data

- UN Recommendations on the Transport of Dangerous Good Dangerous Goods Regulations (DGR) for the air transport (IATA) International Maritime Dangerous Goods Code (IMDG) -
- -

Silicone oil M 20 low viscosity, 20 cSt

article number: 4010

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H227	combustible liquid

Disclaimer

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

