

Printing date 31.07.2018 Revision: 30.10.2017

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

· Article number: TO0085

• CAS Number: 108-88-3 • EC number:

• **EC** number: 203-625-9

• *Index number:* 601-021-00-3

· Registration number 01-2119471310-51-XXXX

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU10 Formulation [mixing] of preparations and/or re-packaging (excluding alloys)

Process category

PROC5 Mixing or blending in batch processes

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC15 Use as laboratory reagent

· Application of the substance / the preparation: Laboratory reagent

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com Internet Web Site: www.scharlab.com

Regional representation:

Scharlab, S.L.

C/Gato Pérez, 33. Pol.Ind. Mas d'en Cisa 08181 Sentmenat (Barcelona) SPAIN

Tel: (+34) 93 745 64 00 - FAX: (+34) 93 715 27 65

email: scharlab@scharlab.com
Internet Web Site: www.scharlab.com

Further information obtainable from: technical department

· 1.4 Emergency telephone number:

Please contact the regional Scharlab distributor/dealer in your country During normal opening times: Scharlab, S.L. (+34) 93 715 18 11

SECTION 2: Hazards identification

- 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS08 health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

(Contd. on page 2)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 1)

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The substance is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.

H361d Suspected of damaging the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

Precautionary statements

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P331 Do NOT induce vomiting.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

- · 2.3 Other hazards
- Results of PBT and vPvB assessment
- *PBT:* Not applicable.*vPvB:* Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.1 Chemical characterisation: Substances
- · CAS No. Description

108-88-3 toluene

- · Identification number(s)
- · EC number: 203-625-9
- · Index number: 601-021-00-3

(Contd. on page 3)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- . Storage
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 4)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 3)

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WEL Short-term value: 384 mg/m³, 100 ppm Long-term value: 191 mg/m³, 50 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 5)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

Form:
Colour:
Colour:
Colour:
Aromatic
Codour threshold:
Not determined.
Not determined.

· Change in condition

Melting point/freezing point: -95 °C Initial boiling point and boiling range: 110-111 °C

· Flash point: 4 °C

· Flammability (solid, gas): Not applicable.

· Ignition temperature: 535 °C

Decomposition temperature: Not determined.
 Auto-ignition temperature: Not determined.

· Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:
Upper:
7 Vol %
7 Vol %

Vapour pressure at 20 °C:
29 hPa

Density at 20 °C:
Relative density
Vapour density
Vapour density
Evaporation rate

1.2 Vol %
7 Vol %

0.87 g/cm³
Not determined.
Not determined.

· Solubility in / Miscibility with

water at 15 °C: 0.5 g/l

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic at 20 °C: 0.6 mPas
Kinematic: Not determined.

9.2 Other information
 No further relevant information available.

SECTION 10: Stability and reactivity

- 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 5)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.
- · LD/LC50 values relevant for classification:

Oral LD50 5,000 mg/kg (rat)
Dermal LD50 12,124 mg/kg (rabbit)
Inhalative LC50/4 h 5,320 mg/l (mouse)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

Suspected of damaging the unborn child.

- STOT-single exposure
- May cause drowsiness or dizziness.
- · STOT-repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)



Printing date 31.07.2018 Revision: 30.10.2017

1294 TOLUENE

TOLUENE

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 6)

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport information

· 14.1 UN-Number

· ADR, IMDG, IATA UN1294

· 14.2 UN proper shipping name

· ADR · IMDG, IATA

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



• Class 3 Flammable liquids.

· Label 3

· 14.4 Packing group

· ADR, IMDG, IATA

· 14.5 Environmental hazards:

· Marine pollutant: No

• 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler):
 EMS Number:
 Stowage Category
 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

Limited quantities (LQ)
Transport category
Tunnel restriction code
D/E

· UN "Model Regulation": UN 1294 TOLUENE, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I Substance is not listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3, 40, 48
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

(Contd. on page 8)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 7)

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- · Department issuing SDS: product safety department
- · Contact: msds@scharlab.com
- Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

(Contd. on page 9)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 8)

Annex: Exposure scenario 1

- · 1 Short title of the exposure scenario Industrial use
- · Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- · Product category PC21 Laboratory chemicals
- · Process category PROC15 Use as laboratory reagent
- · Environmental release category

ERC2 Formulation into mixture

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

Description of the activities / processes covered in the Exposure Scenario
 See section 1 of the annex to the Safety Data Sheet.

- · 2 Conditions of use
- · Duration and frequency

Emission days (days/year): 300

5 workdays/week.

8hrs (full working shift).

Environment

Wastewater is to be treated by a municipal STP. Municipal STP discharge rate <2E3 m3/d.

Estimated substance removal from wastewater via domestic sewage treatment (%): 93.3

Maximum allowable site tonnage based on release following total wastewater treatment removal (kg/day): 7020

- · Physical parameters Readily biodegradable
- · Physical state Fluid
- · Concentration of the substance in the mixture

Raw material.

It covers a percentage of substance in the product up to 100 %

· Used amount per time or activity

Fraction of EU tonnage used in region: 15000

1500 tons per year

Fraction of Regional tonnage locally used: 1

- · Other operational conditions
- Other operational conditions affecting environmental exposure

Fraction released to air from process (initial release previous to MGR): 0.025

Fraction released to residual water from process (initial release previous to MGR): 0.02

Fraction released to ground from process (initial release previous to MGR): 0.0001

Other operational conditions affecting worker exposure

Assumes use at not more than 20 °C above ambient temperature, unless stated differently. Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection
- · Organisational protective measures

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Keep good industrial hygiene.

Users are advised to consider the limits of national occupational exposure or other equivalent values.

Provide a good standard of controlled ventilation (10 to 15 air changes per hour)

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

(Contd. on page 10)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 9)

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Measures for consumer protection Ensure adequate labelling.
- · Environmental protection measures
- · Air No special measures required.
- · Water

The product should not be released into water without pretreatment. An on-site wastewater treatment is recommended. The typical site treatment technology of wastewater achieves removal efficiency (%): (93.3)

- · Soil No special measures required.
- · Notes In case of unintended release of the product: See section 6 of the Safety Data Sheet.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that all wastewater is collected and treated in a wastewater treatment plant.

Ensure that waste is collected and contained.

Recycling possible.

· Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Waste type Partially emptied and uncleaned packaging
- · 3 Exposure estimation
- · Worker (oral)

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Worker (dermal)

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Worker (inhalation)

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

Environment

Detailed information on the estimation of the environmental exposure can be found at http://ecb.jrc.ec.europa.eu/euses/.

· 4 - Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

For the risk assessment, the tools recommended by ECHA can be used.

(Contd. on page 11)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 10)

Annex: Exposure scenario 2

- · 1 Short title of the exposure scenario Laboratory use
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC21 Laboratory chemicals
- · Process category PROC15 Use as laboratory reagent
- · Environmental release category

ERC4 Use of non-reactive processing aid at industrial site (no inclusion into or onto article)

- Description of the activities / processes covered in the Exposure Scenario
 See section 1 of the annex to the Safety Data Sheet.
- · 2 Conditions of use
- · Duration and frequency

Emission days (days/year): 365

5 workdays/week.

8hrs (full working shift).

· Environment

Wastewater is to be treated by a municipal STP. Municipal STP discharge rate <2E3 m3/d.

Estimated substance removal from wastewater via domestic sewage treatment (%): 93.3

Maximum allowable site tonnage based on release following total wastewater treatment removal (kg/day): 280

- · Physical parameters Readily biodegradable
- · Physical state Fluid
- · Concentration of the substance in the mixture

Raw material.

It covers a percentage of substance in the product up to 100 %

· Used amount per time or activity

Fraction of EU tonnage used in region: 15000

1500 tons per year

Fraction of Regional tonnage locally used: 0.002

Annual site tonnage: 3

- · Other operational conditions
- · Other operational conditions affecting environmental exposure

Fraction released to air from process (initial release previous to MGR): 0.5

Fraction released to residual water from process (initial release previous to MGR): 0.5

Fraction released to ground from process (initial release previous to MGR): 0

Other operational conditions affecting worker exposure

Assumes use at not more than 20 °C above ambient temperature, unless stated differently. Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- Worker protection
- · Organisational protective measures

Do not apply industrial sludge to natural soils. Sludge should be incinerated, contained or reclaimed.

Keep good industrial hygiene.

Users are advised to consider the limits of national occupational exposure or other equivalent values.

Provide a good standard of controlled ventilation (10 to 15 air changes per hour)

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

(Contd. on page 12)



Printing date 31.07.2018 Revision: 30.10.2017

Trade name: Toluene, Multisolvent® HPLC grade ACS ISO UV-VIS

(Contd. of page 11)

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Measures for consumer protection Ensure adequate labelling.
- · Environmental protection measures
- · Air No special measures required.
- · Water

The product should not be released into water without pretreatment. An on-site wastewater treatment is recommended. The typical site treatment technology of wastewater achieves removal efficiency (%): (93.3)

- · Soil No special measures required.
- · Notes In case of unintended release of the product: See section 6 of the Safety Data Sheet.
- · Disposal measures

Disposal must be made according to official regulations.

Ensure that all wastewater is collected and treated in a wastewater treatment plant.

Ensure that waste is collected and contained.

Recycling possible.

· Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Waste type Partially emptied and uncleaned packaging
- · 3 Exposure estimation
- · Worker (oral)

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Worker (dermal)

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Worker (inhalation)

The calculated value is smaller than the DNEL.

Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

Environment

Detailed information on the estimation of the environmental exposure can be found at http://ecb.jrc.ec.europa.eu/euses/.

· 4 - Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Whether the downstream user uses the substance / the mixture within the scope of the Exposure Scenario can be determined by means of a technical assessment.

For the risk assessment, the tools recommended by ECHA can be used.